

# United States Patent and Trademark Office

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.usplo.gov /

APPLICATION NO.		FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.	
09/845,770	05/02/2001		Mark A. Kampe	80168-0105	4958	
32658	7590	07/07/2004		EXAMINER		
HOGAN &	HART	SON LLP	BONURA, TIMOTHY M			
ONE TABO		ER, SUITE 1500 ST.	ART UNIT	PAPER NUMBER		
DENVER,	CO 802	02		2114	10	
				DATE MAILED: 07/07/200	_	

Please find below and/or attached an Office communication concerning this application or proceeding.



·····		Amuliant	ion No	Applicant(s)					
•	•	Applicat			)				
	Office Action Summary	09/845,7		KAMPE ET AL.	-/p				
•	omec Action Cammary	Examine		Art Unit	V				
	The MAILING DATE of this communica	Tim Bon		th the correspondence add	ross				
Period fo		idon appears on th	e cover sneet wit	iii tiie con espondence addi	1633				
THE   - External after - If the - If NO - Failu Any (	ORTENED STATUTORY PERIOD FOR MAILING DATE OF THIS COMMUNICATION of time may be available under the provisions of SIX (6) MONTHS from the mailing date of this commun period for reply specified above is less than thirty (30) or period for reply is specified above, the maximum statute to reply within the set or extended period for reply will eply received by the Office later than three months after ad patent term adjustment. See 37 CFR 1.704(b).	ATION.  37 CFR 1.136(a). In no evication.  lays, a reply within the station ory period will apply and voluments.	vent, however, may a re atutory minimum of thirty will expire SIX (6) MON plication to become AB	eply be timely filed  y (30) days will be considered timely.  THS from the mailing date of this com  ANDONED (35 U.S.C. § 133).	nmunication.				
Status									
1)🖾	Responsive to communication(s) filed	on <u>02 May 200</u> 1.							
2a)□	•	non-final.							
3)□	Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under <i>Ex parte Quayle</i> , 1935 C.D. 11, 453 O.G. 213.								
Dispositi	on of Claims								
5)□ 6)⊠ 7)□	Claim(s) 1-29 is/are pending in the application.  4a) Of the above claim(s) is/are withdrawn from consideration.  Claim(s) is/are allowed.  Claim(s) 1-29 is/are rejected.  Claim(s) is/are objected to.  Claim(s) are subject to restriction and/or election requirement.								
Applicat	on Papers								
10)⊠	The specification is objected to by the I The drawing(s) filed on <u>09 August 200</u> : Applicant may not request that any objection Replacement drawing sheet(s) including the oath or declaration is objected to be	1 is/are: a)⊠ according (s) and to the drawing(s) ne correction is requi	be held in abeyan ired if the drawing(	ice. See 37 CFR 1.85(a). (s) is objected to. See 37 CFF	R 1.121(d).				
Priority (	ınder 35 U.S.C. § 119								
<ul> <li>12) Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).</li> <li>a) All b) Some * c) None of:</li> <li>1. Certified copies of the priority documents have been received.</li> <li>2. Certified copies of the priority documents have been received in Application No</li> <li>3. Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).</li> <li>* See the attached detailed Office action for a list of the certified copies not received.</li> </ul>									
2) Notice 3) Infor	t(s)  e of References Cited (PTO-892)  e of Draftsperson's Patent Drawing Review (PTO- mation Disclosure Statement(s) (PTO-1449 or PTO-1449)  er No(s)/Mail Date 5, 6, and 7.		Paper No(s	Summary (PTO-413) s)/Mail Date nformal Patent Application (PTO- 	-152)				

Art Unit: 2114

#### **DETAILED ACTION**

## Claim Rejections - 35 USC § 102

1. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless -

- (e) the invention was described in (1) an application for patent, published under section 122(b), by another filed in the United States before the invention by the applicant for patent or (2) a patent granted on an application for patent by another filed in the United States before the invention by the applicant for patent, except that an international application filed under the treaty defined in section 351(a) shall have the effects for purposes of this subsection of an application filed in the United States only if the international application designated the United States and was published under Article 21(2) of such treaty in the English language.
- 2. Claims 1-3, 5-9, 13-14, 16-20, and 22-29 rejected under 35 U.S.C. 102(e) as being anticipated by Nakamura, U.S. Patent Number 6,446,134.
- 3. Regarding claim 1,
  - a. Regarding the limitation of "using a plurality of components to represent hardware and software in the networked computer system, wherein the plurality of components are high-availability aware," Nakamura discloses a system with a plurality of servers, manager units and communication channels. (Lines 31-34 of Column 4).
  - b. Regarding the limitation of "maintaining a desired level or levels of redundancy of the plurality of components," Nakamura discloses a system wherein the service monitor monitors the state of the network. (Lines 35-36 of Column 4 and Lines 38-40 of Column 2). Nakamura also disclose a system wherein upon fault detection stopping and starting of units occurs in response to a fault notification. (Lines 56-60 of Column 2).
- 4. Regarding claim 2, Nakamura discloses a system with means to recover from failure of a service unit. (Lines 51-55 Column 2).

Art Unit: 2114

5. Regarding claim 3, Nakamura discloses a system with means to recover from failure of a service unit. (Lines 51-55 Column 2).

- 6. Regarding claim 5:
  - c. Regarding the limitation of "detecting a component failure among the plurality of components," Nakamura discloses a system with means to detect a state of a unit for faults. (Liens 21-27 of Column 3).
  - d. Regarding the limitation of "reporting the component failure when appropriate," Nakamura discloses a system with means of notifying mangers units of a fault. (Lines 29-31 of Column 3).
  - e. Regarding the limitation of "conduction a component failure recover procedure," Nakamura discloses a system with means to automatically restart a component if a fault notification exists. (Lines 38-40 of Column 3).
- 7. Regarding claim 6:
  - f. Regarding the limitation of "detecting a component failure among the plurality of components," Nakamura discloses a system with means to detect a state of a unit for faults. (Lines 21-27 of Column 3).
  - g. Regarding the limitation of "reporting the component failure when appropriate,"

    Nakamura discloses a system with means of notifying mangers units of a fault. (Lines

    29-31 of Column 3).
  - h. Regarding the limitation of "conduction a component failure recover procedure," Nakamura discloses a system with means to automatically restart a component if a fault notification exists. (Lines 38-40 of Column 3).

Art Unit: 2114

8. Regarding claim 7:

i. Regarding the limitation of "assigning states to the plurality of components,"

Nakamura discloses a system with a service monitor unit that monitors the state off

service units. (Lines 10-14 of Column 5).

- j. Regarding the limitation of "providing checkpoint services," Nakamura discloses a system with means for a manager unit to monitor the status of a unit. (Lines 21-24 of Column 3).
- k. Regarding the limitation of "monitoring health of the plurality of components," Nakamura discloses a system with means of notifying mangers units of a fault. (Lines 29-31 of Column 3).
- 1. Regarding the limitation of "detecting component failure," Nakamura disclose a system with means to detect a state of a unit for faults. (Lines 21-27 of Column 3).
- m. Regarding the limitation of "recovering from the component failure using checkpoint information," Nakamura discloses a system with network management system fault information in a data format (Lines 17-19 of Column 6), which is used to by service processor to alert management units of a faulty unit and recovery takes place. (Lines 66-67 of Column 6 and Lines 1-9 of Column 7).
- 9. Regarding claim 8, Nakamura discloses a system wherein units are can be in a stop and start state. The stop state being an off-line state when a fault is detected. (Lines 22-25 of Column 5 and Lines 9-11 of Column 6).
- 10. Regarding claim 9:

Art Unit: 2114

n. Regarding the limitation of "isolating a cause of the component failure,"

Nakamura disclose a system wherein the service-monitoring unit will send out a message with a field set to identify if a unit is faulty. (Lines 33-41 of Column 6).

- o. Regarding the limitation of "applying a failure recovery procedure to address the cause," Nakamura disclose a system with to automatically restart a component if a fault notification exists. (Lines 38-40 of Column 3)
- 11. Regarding claim 13, Nakamura discloses a system with an API that can send system messages. (Liens 25-32 of Column 6).
- 12. Regarding claim 14, Nakamura discloses a system that can operate in multiple platforms. (Lines 25-32 of Column 6).
- 13. Regarding claim 16:
  - p. Regarding the limitation of "using a plurality of components to represent hard and software in the networked computer system, wherein the plurality of components are high-availability aware," Nakamura disclose a system with Nakamura discloses a system with a plurality of servers, manager units and communication channels. (Lines 31-34 of Column 4).
  - q. Regarding the limitation of "managing the plurality of components to achieve a desired level or level of redundancy," Nakamura discloses a system wherein the service monitor monitors the state of the network. (Lines 35-36 of Column 4 and Lines 38-40 of Column 2). Nakamura also disclose a system wherein upon fault detection stopping and starting of units occurs in response to a fault notification. (Lines 56-60 of Column 2).

Art Unit: 2114

r. Regarding the limitation of "monitoring health of the networked computer system, including health of the plurality of components and health of the plurality of nodes," Nakamura disclose a system with monitoring capabilities to monitor for faults in a network managed computer system. (Lines 18-25 of Column 2).

- s. Regarding the limitation of "detecting a failure in the networked computer system, including a failure of a component in the plurality of components and a failure of anode in the plurality of nodes," Nakamura disclose a system with means to detect a state of a unit for faults. (Lines 21-27 of Column 3).
- t. Regarding the limitation of "recovering from the failure by performing an appropriate failure recovery procedure," Nakamura disclose a system with to automatically restart a component if a fault notification exists. (Lines 38-40 of Column 3).
- 14. Regarding claim 17, Nakamura disclose a system with can alert a network manager the state of the computer system. (Lines 38-40 of Column 2).
- 15. Regarding claim 18, Nakamura disclose a system with can alert a network manager of a fault in the computer system. (Lines 57-60 of Column 2).
- 16. Regarding claim 19, Nakamura disclose a system wherein the monitoring of the system is conducted with the network management system. (Lines 38-40 of Column 2).
- 17. Regarding claim 20, Nakamura disclose a system with filtering means to filter condition information for the manager. (Lines 25-29 of Column 3). Nakamura disclose a system with to automatically restart a component if a fault notification exists. (Lines 38-40 of Column 3).

Àrt Unit: 2114

18. Regarding claim 22, Nakamura disclose a system with a plurality of server units and a plurality of management units when are connected and operate to notify each other of operating state in the server units. (Lines 59-67 of Column 1 and 1-3 of Column 2).

## 19. Regarding claim 23:

- u. Regarding the limitation of "means for providing component services," Nakamura discloses a system with a plurality of servers, manager units and communication channels. (Lines 31-34 of Column 4).
- v. Regarding the limitation of "means for providing availability management services," Nakamura discloses a system with a manager for the services. (Lines 52-56 of Column 1).
- w. Regarding the limitation of "means for providing distributed system services," Nakamura discloses a system with a network of server connected via the network and managed by a management system. (Lines 58-65 of Column 1).
- x. Regarding the limitation of "means for providing platform specific services," Nakamura discloses a system that can operate in multiple platforms. (Lines 25-32 of Column 6).
- y. Regarding the limitation of "means for providing external management services," Nakamura discloses a system with management units that are connected to the network not directly connected to the servers. (Lines 31-34 of Column 4 and Figure 1).
- z. Regarding the limitation of "wherein the plurality of components are high-availability aware and represent software and hardware in the networked computer

Page 8

Application/Control Number: 09/845,770

Art Unit: 2114

system," Nakamura disclose a system with Nakamura discloses a system with a plurality of servers, manager units and communication channels. (Lines 31-34 of Column 4).

20. Regarding claim 24, Nakamura discloses a system that can operate to operating systems. (Lines 25-32 of Column 6).

#### 21. Regarding claim 25:

- aa. Regarding the limitation of "wherein the plurality of components are high-availability aware and represent software and hardware in the networked computer system," Nakamura disclose a system with Nakamura discloses a system with a plurality of servers, manager units and communication channels. (Lines 31-34 of Column 4).
- bb. Regarding the limitation of "means for maintaining a desired level or level of redundancy of the plurality of components," Nakamura discloses a system wherein the service monitor monitors the state of the network. (Lines 35-36 of Column 4 and Lines 38-40 of Column 2). Nakamura also disclose a system wherein upon fault detection stopping and starting of units occurs in response to a fault notification. (Lines 56-60 of Column 2).

### 22. Regarding claim 26:

- cc. Regarding the limitation of "wherein the plurality of components are high-availability aware and represent software and hardware in the networked computer system," Nakamura disclose a system with Nakamura discloses a system with a plurality of servers, manager units and communication channels. (Lines 31-34 of Column 4).
- dd. Regarding the limitation of "means for maintaining a desired level or level of redundancy of the plurality of components," Nakamura discloses a system wherein the

Art Unit: 2114

service monitor monitors the state of the network. (Lines 35-36 of Column 4 and Lines 38-40 of Column 2). Nakamura also disclose a system wherein upon fault detection stopping and starting of units occurs in response to a fault notification. (Lines 56-60 of Column 2).

- ee. Regarding the limitation of "monitoring health of the networked computer system, including health of the plurality of components and health of the plurality of nodes," Nakamura disclose a system with monitoring capabilities to monitor for faults in a network managed computer system. (Lines 18-25 of Column 2).
- ff. Regarding the limitation of "detecting a failure in the networked computer system, including a failure of a component in the plurality of components and a failure of anode in the plurality of nodes," Nakamura disclose a system with means to detect a state of a unit for faults. (Lines 21-27 of Column 3).
- Regarding the limitation of "recovering from the failure by performing an appropriate failure recovery procedure," Nakamura disclose a system with to automatically restart a component if a fault notification exists. (Lines 38-40 of Column 3).

#### 23. Regarding claim 27:

hh. Regarding the limitation of "wherein the plurality of components are high-availability aware and represent software and hardware in the networked computer system," Nakamura disclose a system with Nakamura discloses a system with a plurality of servers, manager units and communication channels. (Lines 31-34 of Column 4).

#### 24. Regarding claim 28:

Art Unit: 2114

ii. Regarding the limitation of "wherein the plurality of components are high-availability aware and represent software and hardware in the networked computer system," Nakamura disclose a system with Nakamura discloses a system with a plurality of servers, manager units and communication channels. (Lines 31-34 of Column 4).

- jj. Regarding the limitation of "means for maintaining a desired level or level of redundancy of the plurality of components," Nakamura discloses a system wherein the service monitor monitors the state of the network. (Lines 35-36 of Column 4 and Lines 38-40 of Column 2). Nakamura also disclose a system wherein upon fault detection stopping and starting of units occurs in response to a fault notification. (Lines 56-60 of Column 2).
- 25. Regarding claim 29:
  - kk. Regarding the limitation of "wherein the plurality of components are high-availability aware and represent software and hardware in the networked computer system," Nakamura disclose a system with Nakamura discloses a system with a plurality of servers, manager units and communication channels. (Lines 31-34 of Column 4).
  - 11. Regarding the limitation of "means for maintaining a desired level or level of redundancy of the plurality of components," Nakamura discloses a system wherein the service monitor monitors the state of the network. (Lines 35-36 of Column 4 and Lines 38-40 of Column 2). Nakamura also disclose a system wherein upon fault detection stopping and starting of units occurs in response to a fault notification. (Lines 56-60 of Column 2).

Art Unit: 2114

mm. Regarding the limitation of "monitoring health of the networked computer system, including health of the plurality of components and health of the plurality of nodes," Nakamura disclose a system with monitoring capabilities to monitor for faults in a network managed computer system. (Lines 18-25 of Column 2).

- nn. Regarding the limitation of "detecting a failure in the networked computer system, including a failure of a component in the plurality of components and a failure of anode in the plurality of nodes," Nakamura disclose a system with means to detect a state of a unit for faults. (Lines 21-27 of Column 3).
- oo. Regarding the limitation of "recovering from the failure by performing an appropriate failure recovery procedure," Nakamura disclose a system with to automatically restart a component if a fault notification exists. (Lines 38-40 of Column 3).

## Claim Rejections - 35 USC § 103

- 26. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:
  - (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.
- Claims 4, 10-12, 15, and 21 are rejected under 35 U.S.C. 103(a) as being unpatentable over Nakamura as applied to claim 1 above, and further in view of Parks, et al, U.S. Patent Number 6,598,174.
- 28. Regarding claim 4, Nakamura discloses a system with a plurality of servers, manager units and communication channels. Nakamura also disclose a system wherein upon fault

Art Unit: 2114

system by allowing for the continuation of data accessing after a fault.

detection stopping and starting of units occurs in response to a fault notification. (See claim 1 above). Nakamura does not disclose a system with means to migrate a component of the plurality of components from one node to another node. Parks discloses a system with means to migrate data from one unit to another unit to maintain a high level of integrity. (Lines 20-28 of Column 3). It would have been obvious to one of ordinary skill at the time of the invention to combine the network management detection and redundancy of Nakamura with the migration of Park. One of ordinary skill in the art would have combined Park and Nakamura because Nakamura discloses that a unit can be placed in a stop in which the information cannot be accessed by the network. (Lines 42-50 of Column 2). Park's system improves Nakamura's

Page 12

29. Regarding claim 10, Nakamura discloses a system with a plurality of servers, manager units and communication channels. Nakamura also disclose a system wherein upon fault detection stopping and starting of units occurs in response to a fault notification. (See claim 1 above). Nakamura does not disclose a system with means to have nodes with different versions of software. Parks discloses a system with means have different driver modules and configurable logic to handle different drivers (Lines 48-56 of Column 4). It would have been obvious to one of ordinary skill at the time of the invention to combine the network management detection and redundancy of Nakamura with the driver logic of Park. One of ordinary skill in the art would have combined Park and Nakamura because Nakamura discloses that a unit can be placed in a stop in which the information cannot be accessed by the network. (Lines 42-50 of Column 2). Park's system improves Nakamura's system by allowing for the continuation of data accessing after a fault.

Art Unit: 2114

30. Regarding claim 11, Parks discloses a system wherein multiple different drivers can be accessed to respond to a failure. It would be inherent in the system of Parks that there are updates to the drivers.

- 31. Regarding claim 12, Nakamura discloses a system with a plurality of servers, manager units and communication channels. Nakamura also disclose a system wherein upon fault detection stopping and starting of units occurs in response to a fault notification. (See claim 1 above). Nakamura does not disclose a system with means to maintain a specific redundancy level. Parks discloses a system with means providing redundancy for data over a number of data storage devices. (Lines 10-22 of Column 8). It would have been obvious to one of ordinary skill at the time of the invention to combine the network management detection and redundancy of Nakamura with the logic engine of Park. One of ordinary skill in the art would have combined Park and Nakamura because Nakamura discloses that a unit can be placed in a stop in which the information cannot be accessed by the network. (Lines 42-50 of Column 2). Park's system improves Nakamura's system by allowing for the continuation of data accessing after a fault.
- 32. Regarding claim 15, Nakamura discloses a system with a plurality of servers, manager units and communication channels. Nakamura also disclose a system wherein upon fault detection stopping and starting of units occurs in response to a fault notification. (See claim 1 above). Nakamura does not disclose a system with means to maintain a system based on account information. Parks discloses a system with means for a logic engine that contains data for transferring information based on status information, identification of data and data concerning transfer. (Lines 27-38 of Column 4). It would have been obvious to one of ordinary skill at the time of the invention to combine the network management detection and redundancy of

Art Unit: 2114

Nakamura with the logic engine of Park. One of ordinary skill in the art would have combined Park and Nakamura because Nakamura discloses that a unit can be placed in a stop in which the information cannot be accessed by the network. (Lines 42-50 of Column 2). Park's system improves Nakamura's system by allowing for the continuation of data accessing after a fault.

33. Regarding claim 21, Nakamura discloses a system with a plurality of servers, manager units and communication channels. Nakamura also disclose a system wherein upon fault detection stopping and starting of units occurs in response to a fault notification. (See claim 1 above). Nakamura does not disclose a system with means to migrate a component of the plurality of components from one node to another node. Parks discloses a system with means to migrate data from one unit to another unit to maintain a high level of integrity. (Lines 20-28 of Column 3). It would have been obvious to one of ordinary skill at the time of the invention to combine the network management detection and redundancy of Nakamura with the migration of Park. One of ordinary skill in the art would have combined Park and Nakamura because Nakamura discloses that a unit can be placed in a stop in which the information cannot be accessed by the network. (Lines 42-50 of Column 2). Park's system improves Nakamura's system by allowing for the continuation of data accessing after a fault.

#### Conclusion

- 34. Any inquiry concerning this communication or earlier communications from the examiner should be directed to **Tim Bonura**.
  - o The examiner can normally be reached on Mon-Fri: 7:30-5:00, every other Friday off. The examiner can be reached at: 703-305-7762.

Art Unit: 2114

35. If attempts to reach the examiner by telephone are unsuccessful, please contact the examiner's supervisor, **Rob Beausoliel.** 

o The supervisor can be reached on 703-305-9713.

36. The fax phone numbers for the organization where this application or proceeding is

assigned are:

o 703-872-9306 for all patent related correspondence by FAX.

Page 15

37. Information regarding the status of an application may be obtained from the Patent

Application Information Retrieval (PAIR) system. Status information for published applications

may be obtained from either Private PAIR or Public PAIR. Status information for unpublished

applications is available through Private PAIR only. For more information about the PAIR

system, see http://pair-direct.uspto.gov/. Should you have questions on access to the Private

PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

38. Any inquiry of a general nature or relating to the status of this application or proceeding

should be directed to the receptionist whose telephone number is: 703-305-3900.

**39.** Responses should be mailed to:

o Commissioner of Patents and Trademarks

P.O. Box 1450

Alexandria, VA 22313-1450

Tim Bonura Examiner Art Unit 2114

tmb June 14, 2004

PRIMARY EXAMINER

1